

WCO-450-WMB

450-470 MHz Compact
Wall-mount Omni Antenna

Features

- ◆ Waterproof Compact Omni Antenna
- ◆ 450-470 MHz Frequency Band
- ◆ Stainless Steel L-Bracket Mount
- ◆ Outdoor deployments

Specifications

Specifications	
Radiating element	1/4 Wave Element (requires groundplane)
Centre Frequency	460 MHz
Gain	0 dBd / 2.15 dBi
Polarisation	Linear - Vertical
Impedance	50 Ohm
Input Power	20W
VSWR	<1.7:1
Required Groundplane	minimum 100x100mm (or L-bracket as supplied)
Connector	N-Female / N-Female Bulkhead
Dimensions	Sheath approx 116mm + connector

Popular Ordering Options

WCO-450-WMB	WCO 450-470 MHz Omni Antenna with L-Bracket N-Female
WCO-450-WMB-5M195-SM	WCO 450-470 MHz Omni Antenna with L-Bracket 5M BWL195 SMA-Male

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com

EAD
embedded antenna design ltd