



UWB6060

600 MHz to 6 GHz
UWB Omni Antenna

Features

- ◆ Ultra Wideband Omni Antenna
- ◆ Robust Fibreglass Sleeve
- ◆ High Efficiency & High Power Handling
- ◆ Various Mounting Bracket Options
- ◆ Ideal for Jamming, Scanning, Monitoring & Research

Specifications

Frequency range	600 MHz - 6 GHz
Gain	2 dBi (lower band) / 3-4 dBi (upper band)
Polarisation	Linear
Impedance	50 Ohm
VSWR	<2.5:1
Max Power (Single Carrier)	100W
Operating Temp.	-40 to +70 degrees C
Cable / Connector	No cable, N-Female connector
Weight	400g approx.
Dimensions	330 x 70mm (hxd) excluding option mounting brackets

Popular Ordering Options

UWB6060-NF	UWB6060 antenna with N-Female Connector
------------	---

Specifications subject to change without notice.

5 Little Balmer
Buckingham Industrial Park
Buckingham
MK18 1TF
UK

Tel: +44 (0)1280 824055
Fax: +44 (0)1280 817179
Email: sales@ead-ltd.com
Web: www.ead-ltd.com

EAD 
embedded antenna design ltd
Delivering Antenna Innovation